



Stainless Steel Housing optional

Compact Plus 3 Arm

Three-Arm Turnstile

Particularly compact design, especially suitable for high-traffic, controlled outdoor access to sports and leisure facilities as well as pools and beaches.

- extra-compact design
- height-adjustable
- optional fixed-height stainless steel
- pre-assembled delivery
- noise-free operation
- unidirectional or bidirectional
- direction selectable
- high throughput
- lasting quality
- secure traffic separation
- integrated LOGITURN control
- maintenance-free
- wide range of accessories

Functional Description:

The motorized 3-arm turnstile Compact with with designer handrails and its rugged, all-weather powder-coated housing with integrated support is especially suitable for high-traffic, controlled outdoor access.

Ticket readers can be mounted using optional reader supports.

Compact is optionally available in stainless steel with fixed height or as Compact Plus with Designer handlebars.

A wide range of optional accessories allows adaptation to individual requirements.

Application Areas:

- Building Access Control
- Exhibition Centers
- Event Venues / Stadiums
- Public Transport

Technical Characteristics:

Power Supply:	230 V AC / 24V DC
Power Consumption:	max. 50 VA
Storage Temperature:	-40°C bis +40°C
Operating Temperature:	-20°C bis +50°C
Width / Lane Width:	305 mm / 577 mm
Length:	1.550 mm
Height:	1.000 - 1.365 mm
Mass:	45 kg
Material:	
Gehäuse:	Steel, powder-coated, optionally CrNi Steel
Drehstern:	CrNi Steel Type 1.4301

Models:

6COP3AEB: Compact Plus 3-Arm height-adjustable

6COP3AEC: Compact Plus 3-Arm INOX fixed height

Extras:

2P412-N: Presence Sensor

2P414-N: Opto-sensor Release

2P782-N: Climb-over / Crawl-under Protection
(monitoring of star)

2P784-N: Übersteigschutz
(monitoring of lid and star)

21769: Red light 50 mm in Aluminum Ring

21770: Green light 50 mm in Aluminum Ring

21700-N: Reader Holder

Suitable By-Products:

21500K: Palette for mobile deployment

21510K: Guide Rail for Palette

8P408-N: LOGITURN operating console

8P407-N: Housing for operating console

8P409-N: LOGITURN presettable counter

21692: Foundation Assembly for non-sustainable floors

