







ECCO 120 HD

Double portal turnstile with bars, 120° separation, cabinet for reader installation

Especially well suited for outdoor access points in building access control, at sports facilities and for parking garage entrances with high demands on mechanical load capacity.

- Card readers can be installed
- Easy assembly and installation
- Vandal-proof
- Single or bidirectional operation
- Reversible entry direction
- High quality and long service life
- Integrated LOGITURN control unit
- Maintenance-free mechanism
- Easily accessible electronics
- Traffic counter



Gotschlich Maschinenbau Ges.m.b.H

Feistlgasse 6, A-1210 Wien Tel. +43 (1) 2596518 eMail: office@gotschlich.at www.gotschlich.at

Functional Description:

The Ecco 120 HD motorized double portal turnstile with stainless steel drum, barrier grate, guides and feet is especially well suited for outdoor plant access control as well as for stadiums, recreation facilities and garage-to-building transitions.

The housing can accommodate card readers, intercom systems or the like.

The control unit is located in the side housing cabinet for easy maintenance access.

The Ecco 120 HD is suitable for single or bidirectional operation, and its 120° division means high comfort with good traffic separation.

Application Areas:

- Building Access Control
- Trade Shows
- Events & Stadiums

Models:

62229: Ecco 120 HD

Extras/Options:

63500: ECCO Roof BASIC, length 1.500 mm **63530:** ECCO Roof BASIC, length 2.500 mm

63520: ECCO Roof COMFORT, length 1.624 mm **63550:** ECCO Roof COMFORT, length 2.624 mm

62710: CrNi Steel Rain Duct21775: Lane Indicator green21777: Lane Indicator red/green

21781: Opto-sensor Release

62198: Overall Powder-coating in RAL colour

21699: Laser-cut cutouts

62815: Founding assembly kit **22000:** Power-down blocking kit

Suitable By-Products:

62227: Single Turnstile Ecco 120 HB

21501: Reader Stand LS 15421695: Reader Stand LS 140

Technical Characteristics:

Power Supply: 230 V AC 50-60 Hz

Power Consumption: max. 50 VA

Operating Temperature: -25°C to +40°C

Width / Lane Width: 2.901 mm/640 mm

 Length:
 1.300 mm

 Height:
 2.252 mm

Mass:

Reader Interface: Floating Contacts

Material: CrNi Steel Type 1.4301

230 kg

Aluminium powder-coated

