








## FORUM

**Portal Turnstile, full-height,  
120° partition angle,  
acrylic panels**

Particularly suitable for well-frequented entrances with entry and exit operation in indoor areas in public baths and leisure facilities and in factory security as well as in architecturally sophisticated buildings. The fully transparent design fits in sleekly to any architectural design.



- ✓ Transparent design for the architecturally sophisticated interior
- ✓ 120° partition angle, acrylic panels
- ✓ Compact design
- ✓ Bi-directional operation
- ✓ Input direction can be changed
- ✓ Durable quality
- ✓ LOGITURN® Drive Unit
- ✓ Maintenance-free mechanics



## Description

The motor-driven full-height vertical turnstile FORUM with 120° partition angle of the barrier element is made entirely of stainless materials and is particularly suitable for the installation of barriers at area-separating access points in office buildings as well as in swimming pools and leisure facilities.

Easy to service: The lockable cover and the drive and locking unit accessible from above make it particularly easy to service and commission.

## Versions

**6FOR3AE21:** FORUM

## Optional equipment:

- 21781-N:** Light barrier activation
- 21765-N:** Track/release signal LED Dm60mm
- 6P930:** Power supply unit 200 VA, 2x12V
- 22003-N:** Uninterruptible power supply (USV) 1.000 VA
- 22004-N:** USV 1.400 VA

Foundation brackets for non-bearing floors::

- 2K100:** symmetrical bracket
- 2K105:** asymmetric bracket

## Application areas

- Baths and spas
- Plant protection
- Utilities

## Suitable products

- 21501:** Reader stand column 154 mm round
- 21695:** Reader stand column 140x140 mm squared
- 21094:** Pedestrian gate ECCO 2100 with acrylic filling
- 21130MH:** Safety glass panel 10 mm

## Technical features

Power supply:	24 V
Consumption:	max. 50 VA
Storage temperature:	-40°C - +50°C
Operating temperature:	+5°C - +40°C
Width / Passage:	1.610mm / 700mm
Depth:	1.550mm
Hight:	2.282mm
Weight:	230kg
Material:	CrNi steel material 1.4301, Acrylic glass
Communication:	floating contacts

