



TRINITY









Motorized 2- or 3-arm turnstile with payment machine and ticket printer

This access control system with payment machine and ticket printer is equipped with a graphic color display. The clear, comfortable and ergonomic arrangement of the control elements for the customer and operating personnel is especially designed for the specific area of operation.

The automatic check of available coins for change (coin roll changer) and the optional check for paper-stock guarantee a smooth and maintenance free operation. An extra card reader allows access to the facility by employees and enables special control and service functions for the management.

This product is especially suitable for admission payments to amusement parks, attractions, restrooms, public showers and restrooms in restaurants. Particularly well suited for high-(tourist) traffic areas by providing control over facility usage.

- ✓ Maintenance free mechanics with integrated LOGITURN® control for minimal power consumption
- ✓ Large graphic display
- ✓ Life-time quality
- ✓ Traffic counter
- ✓ Display of available coins for change
- ✓ Ticket printer
- ✓ Solid coin box with security lock
- ✓ Bi-directional operation





Description

The motorized turnstile TRINITY in 3- and 2-arm technology (suitable for escape routes) is entirely made of stainless steel. The payment machine includes a coin return unit and ticket printer and is especially suitable for public showers, restrooms, washrooms and amusement parks. The integrated counter offers an exact overview of customer frequency and payments.

The coin box is secured by a special safety lock, thus its exchange can be handled by a regular employee.

Models

6CTR3AEC: TRINITY 3A Stainless Steel

6CTR2AEC: TRINITY 2A Stainless Steel

Extras

- 21021TL-N:** Ticket printer for Trinity (concertina fold)
- 2P411-N:** Sensor start + light barrier release signal
- 2P414-N:** Light barrier release for Logiturn
- Optional:**
- 21024T-N:** TRINITY special personnel card
- 21023T:** TRINITY Fill level monitoring
- 21022T:** TRINITY SET break in & manipulation detection

Other products:

- 21510:** Guardrail on platform
- 21550:** Grating platform

Area of application

- Public restrooms and washrooms
- Recreation facilities
- Amusement parks
- Admission payments
- Attractions
- Indoor and outdoor use

Technical specifications

Power supply	24 V =
Power consumption	50 Wh
Storage temperature	-40°C to +50°C
Operating temperature	-10°C to +50°C
Width/free width	900mm / 570mm
Length	1.000mm
Height	1.647mm
Set-up area	900mm x 1.000mm
Mass	50kg
Material	Stainless steel grade 1.4301 = V2A
Communication	potential free contacts

